

CALUMET




CMS Forward Pixels Geometry Simulation

Neeti Parashar

Purdue University Calumet

Hammond, Indiana, USA
For the CMS Forward Pixel Collaboration



Where to find information

B-tau Physics Group

- http://cmsdoc.cern.ch/cms/Physics/btau/management/top/btau.html
- > Tracker Simulation and Geometry
 - > Coordinators: Filippo Ambroglini (University of Perugia, Italy)

Neeti Parashar (Purdue University Calumet, USA)

- Pixel offline group
 - https://uimon.cern.ch/twiki/bin/view/CMS/PixelOfflineSoftware
 - > Coordinator: Vincenzo Chiochia (University of Zurich)
- > LPC Simulation Group
 - http://www.uscms.org/LPC/lpc_simul/lpc_simulation.html
 - > Coordinators: Daniel Elvira (Fermilab, USA)


Harry Cheung (Fermilab USA)

Institutions

- Purdue University Calumet, Indiana, USA
 - > Neeti Parashar: Coordinator
 - Vesna Cuplov: Post-doctoral fellow
- Kansas State University, Kansas, USA
 - Dmitry Onoprienko: Post-doctoral fellow
- ➤ University of Puerto Rico, Puerto Rico, USA
 - > Xingtao Huang: Post-doctoral fellow
- Northwestern University, Illinois, USA
 - > Victoria Martin: Post-doctoral fellow
- ➤ University of Colorado, Colorado, USA
 - > Max Bunce: Graduate student


Forward Pixel Detector

- Complex design
- > 4 circular disks (in pink)
- > Inner radius = 6 cm
- Outer radius = 15 cm
- > η from 1.5 to 2.25
- Each disk includes24 wedge shaped blades
 - > Turbine like geometry
 - ➤ Each blade is rotated 20° around their radial symmetry axis to increase charge sharing among pixels
 - Provides a hit resolution of ~ 15 μm




Details of Forward Pixel Disks

- Each blade has a set of 45 readout chips (ROC)
 - > 5 different types
 - > 1x5
 - > 2x5
 - > 2x4
 - > 2x3
 - > 1x2
 - Arranged in 7 different arrays on the two sides of the blade
 - An array of ROCs is bump bonded to a corresponding array of silicon sensors on top of it and thus forms a sandwich



Package Structure



Features

- Replaced old geometry description
- ➤ The new geometry is written in XML (eXtensive Markup Language)
- Based on DDD interface (Detector Description Database)
- Conforms to the latest mechanical drawings of the components
- Complete and fully tested successfully for simulation
- > In use by the collaboration